

EconoWriter™

Full-Featured Magnetic Stripe Reader-Writer

For Reading, Writing, and General Card Issuing Operations

Precision Writing on Lo-Co MagStripe Cards

ID TECH EconoWriter™ encodes, reads, & verifies three tracks of MagStripe data in a single swipe. A high resolution tachometer precisely locates encoding; the encoding quality exceeds ISO 7811 standards for new cards. Data density is selectable to 75 or 210 BPI for any track with low coercivity writing operation. An LED provides operation status.

Heavy Duty and Long Life Construction

Full-length guides & a deep card slot ensure accurate card alignment and registration. The low force design of EconoWriter ensures a smooth and easy card swipe which provides an operating life for more than 1,000,000 card swipes. The overall chassis length provides stability during reading and writing operations.

WorkShop™ PC Software

Workshop™ is ID TECH's Windows based PC software utility. It includes all standard and many custom options for reading & writing to a MagStripe low coercivity card. A single window shows the reading & writing format selections for each track. Default selections are available for simple & correct set-ups when encoding ISO, AAMVA or other formats. Database and file operations are supported. Convenient features such as track erasing, card data comparisons, and sequential data writing are included. The EconoWriter communicates via an RS-232 or a USB-RS232 serial COM port interface.

Features and Benefits

- Reads and writes MagStripe cards, tickets, badges, and passbooks in a single swipe
- Reads & writes up to 3 tracks of information and any combination of 210 or 75 bpi densities
- EzWriter provides 1 million read & write operations minimum for heads, tachometer, & electronics
- Workshop™ software is easy to use & guides the user quickly through the reading & writing processes
- Light weight plack plastic housing



IDTECH®

Value through Innovation



IDWA-33XIXX EconoWriter™ Reader-Writer Specifications

Electrical

Operating Voltage:	24VDC +/- 10% (Power Adaptor Module Included).
Power Consumption:	<2AMPS (Triple Track Reading & Writing at High Coercivity).
MTBF:	160,000 Power On Hours.
Encoding/Decoding Density:	75 or 210 BPI, for each track.
Media Coercivity:	250 to 380 oersted
Communication:	RS232, USB-RS232

Environmental

Operating Temperature:	32° F to 122° F (0° C to 50° C). Maximum 95% non-condensing
Storage Temperature:	14° F to 140° F (-10° C to 60° C), non-condensing.

Reliability

Read Head Life:	1,000,000 passes minimum.*
Write Head:	1,000,000 passes minimum.*
Low Amplitude:	Read > 30%@210 BPI, > 40%@75 BPI.
Write Performance:	Meets or exceeds ISO 7811 requirement for new cards.
Warranty:	One year, parts and labor.
Agency:	FCC Class A, CE Class A, and UL Listed.

Mechanical

Card Formats:	ISO/ANSI, AAMVA, and "USER" (Custom).
Available Configurations:	Tracks 1 and 2 or Tracks 1, 2, and 3.
Swipe Speed (Reading):	5 to 55 inches per second.
Swipe Speed (Writing):	5 to 35 inches per second.
Media Thickness:	.007 to .045 inches.
Weight:	20 oz (0.6 kg).
Dimensions (HxWxL):	2.6 inches (67 mm) x 2.5 inches (64 mm) x 8.0 inches (204 mm) (includes feet)
Color:	Black.
Housing:	Plastic.



Workshop Software Application Features

Write	Writes data to a card in the Card Type format
Read	Reads card data and displays the data in Track boxes
Compare	Compares multiple cards to a single reference card
Erase	Erases the selected tracks of data on a card
Sequential Write	Writes both fixed and/or sequential data to a card
Write from File	Writes to each card the next record from a file
Read to File	Reads a card and enters the data as a record into a file
Database Write	Writes cards from a database CSV file and Setup file
Card Type	Provides card format selection based on Setup and Standards
— ISO	Selects 7811 ISO Standard card format
— AAMVA	Selects AAMVA standard, based on ISO Standards
— USER	Selects the card format from settings in Setup USER tab
— RAW	Reads and writes data and displays in a Hexadecimal format
— Setup	Provides selections and settings of formats and track parameters
— Leading Zero	Sets number of leading zeros before the Start Sentinel
— BPI Setting	Selects individual track data density (75 or 210 bits/inch)
— Start Sentinel	Selects the Start Sentinel character for the individual tracks
— End Sentinel	Selects the End Sentinel character for the individual tracks
— Bits/Character	Selects the number of bits per character for individual tracks
— Parity	Selects character parity bit logic for individual tracks
— -Default	Resets the parameters and settings to the standard norms

* All reliability numbers are based on operation in a benign environment.

IDTECH®
Value through Innovation

Corporate Headquarters:

10721 Walker Street Cypress, California 90630
(714) 761-6368 Fax: (714) 761-8880
sales@idtechproducts.com

International Sales Office for Canada & South America:

+450 465 5261 (Canada)
robertop@idtechproducts.com

European Sales Office:

+33 5 65 50 28 59 (France)
iann@idtechproducts.com

ISO 9001 : 2000 Certified





800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service

Our Brands




MOTOROLA

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)